

Hydraulically Reversible MB Plough

B.L Agriculture



FEATURES

- Strong thick walled box Section frame.
- Body extension provision from 2-3 mould boards (pairs).
- Large inter body and under frame clearance.
- Provision for angle adjustment.
- Axle housing pipe.
- Provision of shear bolt.
- Specially heat treated parts and polished mould board.
- Reliable turn over device.
- Adjustable stray rod assembly
- Shock absorbing shaft

Hydraulically Reversible MB Plough

B.L Agriculture

MODELNUMBER	2 BOTTOM	3 BOTTOM
REQUIRED POWER HP	50 - 75	80 - 90
TOTAL LENGTH OF LOW (MM)	2100 mm	3000 mm
NO. OF BOTTOMS	2	3
WORKING WIDTH OF EACH BOTTOM (mm)	300 / 350 / 400	300 / 350 / 400
UNDER FRAME POINT CLEARANCE (MM)	600	600
HORIZONTAL SUCTION (MM)	10 to 25	10 to 25
VERTICAL SUCTION (PENETRATION PITCH)	10 to 20	10 to 20
	200 - 330 (8"-13")	200 - 330 (8"-13")
WORKING DEPTH (MIN-MAX) mm	±30 mm	±30 mm
WORKING WIDTH	600 mm	900 mm
PENETRATION PITCH	620 mm	620 mm
APPROX. WEIGHT	450 Kg.	660 Kg.

F-829, 3rd phase Near Mercedes service center
Sitapura Industrial Area, Jaipur, RAJ.

Email- blagriculture@gmail.com

9414018891,9462573334

