

Mounted MB Plough

B.L Agriculture



FEATURES

- The under frame and unit-to-unit clearance are adequate to cope with trashy conditions.
- Adding an extra furrow or repositioning units to allow for extra clearance is quick and easy.
- The plough has special wear-resistance steel bottoms with bar points for toughest ploughing jobs.
- Bar points bottoms ensure longer life as they can be extended or reserved or re-used till the last possible length.

Mounted MB Plough

B.L Agriculture

SIZE	2 FURROW	3 FURROW
FRAME	65 x 65 mm Box with 50 mm square	65 x 65 mm Box with 50 mm square
TYPE	36 mm profile cut single piece	36 mm profile cut single piece
LENGTH	1310 mm	2000 mm
WIDTH	740 mm	740 mm
HEIGHT	1050 mm	1100 mm
BLADE	10 mm	10 mm
MOULD BOARD PLATE	8 mm	8 mm
SHOVEL	45 x 25 mm Bar {EN-42 Forged}	45 x 25 mm Bar {EN-42 Forged}
3 POINT LINKAGE	65 x 16 mm Flat & 32 mm square	65 x 16 mm Flat & 32 mm square
CLAMP	125 x 50 mm	125 x 50 mm
WIDTH OF CUT (MAXIMUM)	615 mm	915 mm
DEPTH OF CUT (MAXIMUM)	350 mm	350 mm
POWER REQUIRED (HP)	40 HP	55 HP & Above
APPROX WEIGTH	240 Kg.	355 Kg.

F-829, 3rd phase Near Mercedes service center
Sitapura Industrial Area, Jaipur, RAJ.

Email- blagriculture@gmail.com

9414018891,9462573334

