

Mounted Offset Disc Harrow

B.L Agriculture



FEATURES

- High quality Boron steel discs.
- Easily transportable- as it gets easily attached and mounted.
- Tillage depth of the harrow is 6 inch.
- Maintenance is easy but need to be scheduled.

Mounted Offset Disc Harrow

B.L Agriculture

	6X6	7X7	8X8	9x9	10x10
No. OF DISCS	12	14	16	18	20
FRAME	75 x 10 mm Angle with 100 x 50 mm Channel	75 x 10 mm Angle with 100 x 50 mm Channel	75 x 10 mm Angle with 100 x 50 mm Channel	75 x 10 mm Angle with 100 x 50 mm Channel	75 x 10 mm Angle with 100 x 50 mm Channel
GANG BOLT LENGTH	32 mm Central square Solid Bar 2030 mm	32 mm Central square Solid Bar 2080 mm	32 mm Central square Solid Bar 2130 mm	32 mm Central square Solid Bar with split gangs 2230 mm	32 mm Central square Solid Bar with split gangs 2280 mm
HEIGHT DISTANCE BETWEEN DISCS	1150 mm with 560 mm Disc 1200 mm with 610 mm Disc	1150 mm with 560 mm Disc 1200 mm with 610 mm Disc	1150 mm with 560 mm Disc 1200 mm with 610 mm Disc	1150 mm with 560 mm Disc 1200 mm with 610 mm Disc	1150 mm with 560 mm Disc 1200mm with 610 mm Disc
MOUNTING	CAT. I / II (Optional)	CAT. I / II (Optional)	CAT. I / II (Optional)	CAT. I / II (Optional)	CAT. I / II (Optional)
DISC DIAMETER (mm)	560 / 610 (Optional)	560 / 610 (Optional)	560 / 610 (Optional)	560 / 610 (Optional)	560 / 610 (Optional)
TYPE OF DISCS	Notched in Front & Plain in Rear	Notched in Front & Plain in Rear	Notched in Front & Plain in Rear	Notched in Front & Plain in Rear	Notched in Front & Plain in Rear
BEARING HUBS (Nos.)	4	4	6	8 (Split Gang Arrangement)	8 (Split Gang Arrangement)
WIDTH OF CUT	1350 - 1400 mm	1600 - 1650 mm	1800 - 1850 mm	2000 - 2100 mm	2250 - 2300 mm
POWER REQUIRED	35 HP	40 - 45 HP	45 - 50 HP	50 - 55 HP	55 - 60 HP
APPROX WEIGHT (KG)	425 with 610 mm Disc	465 with 610 mm Disc	510 with 610 mm Disc	570 with 610 mm Disc	625 with 610 mm Disc

F-829,3rd phase Near Mercedes service center Sitapura , Jaipur, RAJ.

Email- blagriculture@gmail.com

9414018891,9462573334